



Takeuchi mini excavators provide a range of machines built with high specification and reliable performance. With a proven reputation with plant hire, contractors and builders Takeuchi diggers are now the popular choice on site.

Takeuchi minis - Built for the Job.



Takeuchi hydraulic breakers provide genuine hydraulic breaking performance to match carrier capability. Engineered to match Takeuchi mini excavators as well as alternative carriers, the range of Takeuchi breakers gets powerful on-site breakout force.

Breakout with Takeuchi breakers.



Takeuchi compact tracked loaders are unique in design and performance. Designed and engineered as a high performance tracked alternative, the TL range has a proven reputation. Higher specifications, powerful bucket breakout force and unmatched operating capacity.

Get Loaded with Takeuchi track loaders.



The powerful Takeuchi 14 tonne is the largest of our range of excavators. Engineered with high performance and high specification for the most sophisticated operators, the TB1140 combines compact size with its unique offset boom, to get the Takeuchi TB1140 into operating places other conventional 14 tonne machines can't get.

Takeuchi TB1140 – a compact 14 tonne

COMPACT EXCAVATORS



| TB108 | |
|---------------------------|----------|
| Operating Weight (kg) | 880 |
| Width Canopy ROPS (mm) | 740 |
| Max Dig Depth (mm) | 1680 |
| Max Bucket Dig Force (kN) | 10.2 |
| kW/RPM | 7.1/2400 |
| Travel Speed (km/h) | 2.0/3.9 |
| Auxiliary Flow (l/min) | 22 |

| TB014 | |
|----------------------------------|-----------|
| Operating Weight Cab/Canopy (kg) | 1525/1410 |
| Width (mm) | 980 |
| Max Dig Depth (mm) | 2135 |
| Max Bucket Dig Force (kN) | 12.1 |
| kW/RPM | 9.0/2200 |
| Travel Speed (km/h) | 1.9/3.7 |
| Auxiliary Flow (l/min) | 35 |

| TB016 | |
|----------------------------------|-----------|
| Operating Weight Cab/Canopy (kg) | 1800/1660 |
| Width (mm) | 980 |
| Max Dig Depth (mm) | 2375 |
| Max Bucket Dig Force (kN) | 13.1 |
| kW/RPM | 10.1/2200 |
| Travel Speed (km/h) | 2.3/4.2 |
| Auxiliary Flow (l/min) | 35 |

| TB23R | |
|----------------------------------|-----------|
| Operating Weight Cab/Canopy (kg) | 2640/2480 |
| Width (mm) | 1400 |
| Max Dig Depth (mm) | 2560 |
| Max Bucket Dig Force (kN) | 19 |
| kW/RPM | 13.9/2300 |
| Travel Speed (km/h) | 2.4/4.2 |
| Auxiliary Flow (l/min) | 40 |

| TB125 | |
|---------------------------|-----------|
| Operating Weight (kg) | 2900 |
| Width (mm) | 1450 |
| Max Dig Depth (mm) | 1480 |
| Max Bucket Dig Force (kN) | 20.6 |
| kW/RPM | 16.8/2300 |
| Travel Speed (km/h) | 2.7/4.8 |
| Auxiliary Flow (l/min) | 52 |

| TB235 | |
|---------------------------|-----------|
| Operating Weight (kg) | 3530 |
| Width (mm) | 1630 |
| Max Dig Depth (mm) | 3400 |
| Max Bucket Dig Force (kN) | 27 |
| kW/RPM | 21.5/2400 |
| Travel Speed (km/h) | 2.6/5 |
| Auxiliary Flow (l/min) | 61 |

| TB145 | |
|---------------------------|-----------|
| Operating Weight (kg) | 4740 |
| Width (mm) | 1840 |
| Max Dig Depth (mm) | 3500 |
| Max Bucket Dig Force (kN) | 36.5 |
| kW/RPM | 27.3/2300 |
| Travel Speed (km/h) | 2.7/5 |
| Auxiliary Flow (l/min) | 96 |

| TB175 | | TB175W | |
|---------------------------|---------|---------|--|
| Operating Weight (kg) | 7280 | 7905 | |
| Width (mm) | 2150 | 2330 | |
| Max Dig Depth (mm) | 4590 | 4055 | |
| Max Bucket Dig Force (kN) | 52.7 | 52.7 | |
| kW/RPM | 45/2300 | 53/2200 | |
| Travel Speed (km/h) | 3/5.5 | 4.5/26 | |
| Auxiliary Flow (l/min) | 110 | 69 | |

COMPACT EXCAVATORS



| TB138FR | |
|---------------------------|-----------|
| Operating Weight (kg) | 3860 |
| Width (mm) | 1740 |
| Max Dig Depth (mm) | 3420 |
| Max Bucket Dig Force (kN) | 26.5 |
| kW/RPM | 20.5/2300 |
| Travel Speed (km/h) | 2.5/4.7 |
| Auxiliary Flow (l/min) | 64 |

| TB153FR | |
|---------------------------|-----------|
| Operating Weight (kg) | 5615 |
| Width (mm) | 2000 |
| Max Dig Depth (mm) | 3900 |
| Max Bucket Dig Force (kN) | 36.3 |
| kW/RPM | 28.9/2400 |
| Travel Speed (km/h) | 2.8/5 |
| Auxiliary Flow (l/min) | 61 |

| TB180FR | |
|---------------------------|-----------|
| Operating Weight (kg) | 8350 |
| Width (mm) | 2300 |
| Max Dig Depth (mm) | 4545 |
| Max Bucket Dig Force (kN) | 53.2 |
| kW/RPM | 45.1/2200 |
| Travel Speed (km/h) | 2.7/5.4 |
| Auxiliary Flow (l/min) | 69.5 |

14 TONNE EXCAVATORS



| TB1140 | |
|---------------------------|-----------|
| Operating Weight (kg) | 14,230 |
| Width (mm) | 2490 |
| Max Dig Depth (mm) | 2815 |
| Max Bucket Dig Force (kN) | 4990 |
| kW/RPM | 62.2/2050 |
| Travel Speed (km/h) | 3.0/5.3 |
| Auxiliary Flow (l/min) | 113 |

COMPACT TRACK LOADERS



| | TL120 | TL130 | TL140 | TL150 |
|----------------------------|-----------|-----------|-----------|---------|
| Operating weight (kg) | 2625 | 3325 | 4275 | 4775 |
| Width without bucket (mm) | 1470 | 1580 | 1770 | 1860 |
| Height (mm) | 1970 | 2235 | 2270 | 2320 |
| Tipping Load (kg) | 1600 | 2100 | 2700 | 3200 |
| RPM/kW | 38.5/2800 | 49.2/2450 | 60.3/2500 | 72/2200 |
| Bucket Breakout Force (kN) | 28.4 | 29.9 | 32.9 | 38.7 |
| Auxiliary Flow (l/min) | 63 | 126 | 136 | 150 |

TRACKED CARRIERS



| TCR50 | |
|-------------------------|-----------|
| Weight (kg) | 5680 |
| Width (mm) | 2000 |
| Skip height tipped (mm) | 3625 |
| Max safe load (kg) | 3700 |
| kW/RPM | 67.7/2500 |
| Tip angle | 65° |
| Travel speed (km/h) | 7/9 |

HYDRAULIC BREAKERS



| | TKB-51 | TKB-71 | TKB-101 |
|--------------------------------------------|-----------|----------|----------|
| Body weight (kg) | 32 | 56 | 100 |
| Operating weight (inc chisel bracket) (kg) | 50 | 90 | 160 |
| Overall body length (mm) | 865 | 1105 | 1304 |
| Impact blows per minute (bpm) | 1250-2150 | 580-1100 | 800-1430 |
| Carrier weight (tonnes) | 0.7-1.0 | 1.0-2.5 | 2.0-3.8 |

| | TKB-301 | TKB-401 | TKB-801 |
|--------------------------------------------|----------|----------|-----------|
| Body weight (kg) | 150 | 220 | 410 |
| Operating weight (inc chisel bracket) (kg) | 270 | 400 | 705 |
| Overall body length (mm) | 1590 | 1800 | 2080 |
| Impact blows per minute (bpm) | 600-1100 | 500-1050 | 440-800 |
| Carrier weight (tonnes) | 4.0-9.0 | 6.0-10.0 | 10.0-17.0 |